



## EPS 16 PORT POWER DISTRIBUTION UNIT

### FEATURES:

- Built-in active PFC function
- High efficiency up to 92%
- Forced air cooling by built-in DC fan
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Rack or Wall Mountable

### CERTIFICATES:

- Conforms to ANSI-UL 62368-1
- Certified to CSA C22.2 No. 62368-1
- EMC: FCC 47 CFR Part 15B, ISED ICES-003 Class A



### APPLICATIONS:

- GPON Remote ONT Power
- Distributed Antenna Systems
- L.E.D Lighting
- Security / Access Control
- Building Controls

### PART NUMBERS:

#### EPS - 16 - x - y

- x = (1)120V-240V Input , (2) High Voltage DC Input
- y = (0) No Splitter , (1) 2x16 LC/APC Splitter

### OUTPUT OPTIONS:

- 16 12AWG-24AWG Interfaces
- 98W Per Output
- 56VDC
- Optional Integrated 1x16, 2x16 Fiber Optic Splitter

### INPUT:

- 120VAC - 240VAC
- 12A / 7.5A 50/60Hz
- 6' C19-NEMA 5-15P Provided
- Optional High Voltage DC Interface

### DIMENSIONS:

- 16 PORT 100W MODEL: (1RU) 1.75"H X 16"D X 17"W / 16.2 LBS

### ENVIRONMENT:

- Working Temp : -35 – +30 Degrees C
- Working Humidity: 20%-90% RH non-condensing
- Storage Temp: HUMIDITY: -40 - +85 Degrees C, 10% - 95% RH
- Temp Coefficient: +/-0.003% / Degrees C (0-50 Degrees C)
- Vibration: 10 – 500Hz, 2G 10min./1cycle, 60min. each along X,Y,Z