

EPS 8 PORT POWER DISTRIBUTION UNIT



FEATURES:

- Built-in active PFC function
- High efficiency up to 92%
- Forced air cooling by built-in DC fan
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Rack or Wall Mountable

CERTIFICATES:

- Conforms to ANSI-UL 62368-1
- Certified to CSA C22.2 No. 62368-1
- EMC: FCC 47 CFR Part 15B, ISED ICES-003 Class A



APPLICATIONS:

- GPON Remote ONT Power
- Distributed Antenna Systems
- L.E.D Lighting
- Security / Access Control
- Building Controls

PART NUMBERS:

EPS - 8 - x - y

- x = (1)120V-240V Input , (2) High Voltage DC Input
- y = (0) No Splitter , (1) 1x8 SC/APC Splitter

OUTPUTS:

- 8 12AWG-24AWG Interfaces
- 98W Per Output
- 56VDC
- Optional Integrated 1x8, 2x8 Fiber Optic Splitter

INPUT:

- 120VAC - 240VAC
- 12A / 7.5A 50/60Hz
- 6' C19-NEMA 5-15P Provided
- Optional High Voltage DC Interface

DIMENSIONS:

- 8 PORT 100W MODEL: 18"H X 5.5"D X 16"W / 9.2 LBS

ENVIRONMENT:

- Working Temp : -35 – +30 Degrees C
- Working Humidity: 20%-90% RH non-condensing
- Storage Temp: HUMIDITY: -40 - +85 Degrees C, 10% - 95% RH
- Temp Coefficient: +/- .003% / Degrees C (0-50 Degrees C)
- Vibration: 10 – 500Hz, 2G 10min./1cycle, 60min. each along X,Y,Z