



EPS - Intelligent Power Series 32 32 PORT POWER DISTRIBUTION UNIT




FEATURES:

- High efficiency up to 92%
- Forced air cooling by built-in DC fan
- Protections: Short circuit / Overload / Over

CERTIFICATES:

- Conforms to ANSI-UL 62368-1
- Certified to CSA C22.2 No. 62368-1
- EMC: FCC 47 CFR Part 15B, ISED ICES-003 Class A



APPLICATIONS:

- GPON Remote ONT Power
- Distributed Antenna Systems
- L.E.D Lighting
- Security / Access Control
- Building Controls

D5FH'BIA69FG:

DG!'&'!_'!m'!n

- 32 12AWG-24AWG 6SULDRDG Interfaces
- 94W Per Output
- 56VDC
- Optional Integrated 1x32, 2x32 Fiber Optic Splitter

OUTPUT OPTIONS:

- (2) 120VAC - 240VAC
- (2) 12A / 7.5A 50/60Hz
- (2) 6' C19-NEMA 5-15P Provided
- Optional High Voltage DC Interface

INPUT CDH-CB%:

- (F) 120VAC - 240VAC
- (F) 12A / 7.5A 50/60Hz
- (F) 6' C19-NEMA 5-15P Provided
- Optional High Voltage DC Interface

INPUT CDH-CB%:

- (F) 120VAC - 240VAC
- (F) 12A / 7.5A 50/60Hz
- (F) 6' C19-NEMA 5-15P Provided
- Optional High Voltage DC Interface

DEMENSIONS:

- 32 PORT 100W MODEL: (2RU) 3.50"H X 16"D X 17"W / 23.2 LBS

ENVIRONMENT:

- Working Temp : -35 – +30 Degrees C
- Working Humidity: 20%-90% RH non-condensing
- Storage Temp: HUMIDITY: -40 - +85 Degrees C, 10% - 95% RH
- Temp Coefficient: +/- .003% / Degrees C (0-50 Degrees C)
- Vibration: 10 – 500Hz, 2G 10min./1cycle, 60min. each along X,Y,Z